

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

1. **(Currently amended)** ~~A method for performing a downshift in a transmission system including transmission system comprising~~ first and second rotatable shafts, said first shaft having a longitudinal axis, and means for transferring drive from one of the shafts to the other shaft comprising first and second gear wheels each rotatably mounted on the first shaft and having drive formations formed thereon, a selector assembly for selectively transmitting torque between the first shaft and the first gear wheel and between the first shaft and the second gear wheel, wherein the selector assembly comprises an actuator assembly and first and second sets of engagement members, wherein each engagement member includes a first engagement face for engaging the first gear wheel and a second engagement face for engaging the second gear wheel, said actuator assembly including a shift fork assembly arranged to move each of the first and second sets of engagement members that are moveable into and out of engagement with the first and second gear wheels independently of each other, said actuator assembly being arranged to move the first and second sets of engagement members in first and second directions along the longitudinal axis of the first shaft into and out of engagement with the first and second gear wheels independently of each other, the arrangement being such that, and when one of the first and second gear wheels is selected by the first and second sets of engagement members, the backlash between the first and second sets of engagement members and the drive formations when moving between acceleration and deceleration is less than or equal to four degrees, and the transmission being further arranged such that when the first gear is selected by the first and second sets of engagement members and a driving force is transmitted the second set of engagement members drivingly engages the selected first gear wheel, when a driving force is transmitted, one of the first and second sets of engagement members drivingly engages the engaged gear wheel, and the other first set of engagement members is then in an unloaded condition, wherein the shift fork assembly is arranged to move the unloaded first set of engagement members into driving engagement with the second gear wheel to effect a gear change wherein the actuator assembly moves the unloaded set of engagement members into driving engagement with the unengaged gear wheel to effect a downshift.

2. **(Currently amended)** ~~The method~~ A transmission system according to claim 1, wherein the selector assembly is arranged such that when the first gear wheel is engaged by the first and second sets of engagement members and a braking force is transmitted the first set of engagement members drivingly engages the engaged gear wheel, and the second set of engagement members is in an unloaded condition, and when a driving force is transmitted the second set of engagement members drivingly engages the engaged gear wheel, and the first set of engagement members is then in an unloaded condition.

3. **(Currently amended)** ~~The method~~ A transmission system according to claim 1, wherein the actuator assembly is arranged to bias the loaded set of engagement members towards the unengaged gear wheel without disengaging the loaded set of engagement members from the engaged gear wheel.

4. **(Currently amended)** ~~The method~~ A transmission system according to claim 1, wherein the first and second sets of engagement members are arranged to rotate, in use, with the first shaft.

5. **(Currently amended)** ~~The method~~ A transmission system according to claim 1, wherein the first shaft is an input shaft and the second shaft is an output shaft and drive is transferred from the input shaft to the output shaft.

6. **(Canceled)**

7. **(Currently amended)** ~~The method~~ A transmission system according to claim 1, wherein the drive formations on the first and second gear wheels comprise a first and second groups of dogs respectively.

8. **(Currently amended)** ~~The method~~ A transmission system according to claim 7, wherein the first and second groups of dogs each comprise between two and eight dogs, evenly distributed on the first and second gears respectively.

9. **(Currently amended)** ~~The method~~ A transmission system according to claim 8, wherein the first and second groups of dogs each comprise between two and four dogs, and preferably three dogs.

10. **(Currently amended)** ~~The method~~ A transmission system according to claim 1, wherein the first and second sets of engagement members comprise between two and eight members.

11. (**Currently amended**) ~~The method~~ A transmission system according to claim 10, wherein the first and second sets of engagement members comprise between two and four members, and preferably three members.

12. (**Currently amended**) ~~The method~~ A transmission system according to claim 1, wherein the first shaft comprises keyways arranged such that the first and second sets of engagement members can slide axially along the keyways and to radially restrain the positions of the sets of engagement members.

13. (**Currently amended**) ~~The method~~ A transmission system according to claim 12, wherein a cross-section of the keyways is one of T-shaped, slotted, and dovetailed.

14. (**Currently amended**) ~~The method~~ A transmission system according to claim [[1]]35, wherein the actuator assembly comprises at least one resiliently deformable means for connecting a shift fork arranged to move to at least one of the first and second sets of engagement members, said at least one resiliently deformable means being arranged to move at least one of the first and second sets of engagement members into engagement with the first and second gear wheels in response to movement of the shift fork ~~when the engagement members are in unloaded conditions.~~

15. (**Currently amended**) ~~The method~~ A transmission system according to claim 14, wherein the at least one resiliently deformable means is arranged to bias at least one of the first and second sets of engagement members towards the first or second gear wheel when the engagement members are drivingly engaged with a gear wheel.

16. (**Currently amended**) ~~The method~~ A transmission system according to claim 14, wherein the actuator assembly comprises first and second resiliently deformable means connected to the first and second sets of engagement members respectively and to the shift fork such that the first resiliently deformable means acts on the first set of engagement members and the shift fork, and the second resiliently deformable means acts on the second set of engagement members and the shift fork.

17. (**Currently amended**) ~~The method~~ A transmission system according to claim 14, wherein the at least one resiliently deformable means is connected to the first and second sets of engagement members such that the resiliently deformable means acts on both the first and second sets of engagement members and the shift fork.

18. **(Currently amended)** ~~The method~~ A transmission system according to claim 12, wherein ~~the~~ members of the first and / or second sets of engagement members can perform limited axial movement relative to each other in the keyways.

19. **(Currently amended)** ~~The method~~ A transmission system according to any one of claims 14-18, wherein the resiliently deformable means ~~[[is]]~~includes a spring.

20. **(Currently amended)** ~~The method~~ A transmission system according to claim ~~[[25]]~~19, wherein the disc spring comprises a plurality of arms, each arm having a first part that extends circumferentially around a portion of the disc spring and a second part that extends substantially radially inwards.

21. **(Canceled)**

22. **(Currently amended)** ~~The method~~ A transmission system according to claim 1, wherein the drive formations are arranged such that they do not extend beyond the outside diameter of the gear wheels.

23. **(Currently amended)** ~~The method~~ A transmission system according to claim 8, wherein the first and second groups of dogs each comprise three dogs.

24. **(Currently amended)** ~~The method~~ A transmission system according to claim 10, wherein the first and second sets of engagement members comprise three members.

25. **(Currently amended)** ~~The method~~ A transmission system according to claim 19, wherein the resiliently deformable means is a disc spring.

26-34. **(Canceled)**

35. **(New)** A transmission system according to Claim 1, wherein the first and second engagement faces each have a retention angle in the range of 2.5 to 15 degrees.

36. **(New)** A transmission system according to claim 1, wherein each engagement member includes a body that is substantially rigid such that the first and second engagement faces are arranged in a fixed relationship to one another.

37. **(New)** A transmission system according to claim 1, wherein the transmission system includes at least one further shaft.

38. **(New)** A method for performing a decelerating downshift in a transmission system, said method including:

providing a transmission system having first and second rotatable shafts, said first shaft having a longitudinal axis;

providing first and second gear trains for transferring drive from one of the shafts to the other shaft, the first gear train including a first gear wheel rotatably mounted on selectively transmitting torque between the second gear wheel and the first shaft via a selector assembly including an actuator assembly having a shift fork assembly, and first and second sets of engagement members by

engaging the second gear wheel with the first set of engagement members such that each of the engagement members in the first set engages the second gear wheel with a first engagement face, and by

engaging the second gear wheel with the second set of engagement members such that each of the engagement members in the second set engages the second gear wheel with a first engagement face, and such that backlash between the first and second sets of engagement members and the drive formations when moving between acceleration and deceleration is less than or equal to four degrees; and

starting from a position wherein the second set of engagement members drivingly engages the second gear wheel and the first set of engagement members is in an unloaded condition with respect to the second gear wheel, initially moving the unloaded first set of engagement members along the longitudinal axis of the first shaft by action of the fork assembly into engagement with the first gear wheel such that each of the engagement members in the first set engages the second gear wheel with a second engagement face, thereby transmitting torque between the first shaft and the first gear wheel to effect the gear change.

39. (New) A method according to claim 38, including moving the second set of engagement members into engagement with the first gear wheel after the first set of engagement members engages the first gear wheel, such that each of the engagement members in the second set engages the second gear wheel with a second engagement face.

40. (New) A method according to claim 38, wherein engaging the second gear wheel with the first and second sets of engagement members includes moving the first and second sets of engagement members in a first direction along the longitudinal axis of the first shaft into engagement with the second gear wheel by action of the shift fork assembly, and wherein moving the first set of engagement members into engagement with the first gear wheel includes moving

the first set of engagement members in a second direction along the longitudinal axis of the first shaft into engagement with first gear wheel by action of the shift fork assembly.

41. (New) A method according to claim 38, including providing a transmission system with at least one further shaft.

42. (New) A method for performing a kickdown downshift in a transmission system, said method including:

providing a transmission system having first and second rotatable shafts, said first shaft having a longitudinal axis,

providing first and second gear trains for transferring drive from one of the shafts to the other shaft, the first gear train including a first gear wheel rotatably mounted on the first shaft and the second gear train includes a second gear wheel rotatably mounted on the first shaft, said first and second gear wheels having drive formations formed thereon, and said second gear wheel being part of a higher gear than the first gear wheel;

selectively transmitting torque between the second gear wheel and the first shaft via a selector assembly including an actuator assembly, and first and second sets of engagement members by

engaging the second gear wheel with the first set of engagement members such that each of the engagement members in the first set engages the second gear wheel with a first engagement face, and by

engaging the second gear wheel with the second set of engagement members such that each of the engagement members in the second set engages the second gear wheel with a first engagement face;

starting from a position wherein the first set of engagement members drivingly engages the second gear wheel and the second set of engagement members is in an unloaded condition with respect to the second gear wheel;

briefly interrupting torque to the transmission system to disengage the first set of engagement members from the second gear wheel; and

subsequently moving the unloaded second set of engagement members along the longitudinal axis of the first shaft into engagement with the first gear wheel such that each of the engagement members in the second set engages the second gear wheel with a

second engagement face thereby transmitting torque between the first shaft and the first gear wheel, to effect the gear change.

43. **(New)** A method according to claim 42, including moving the first set of engagement members into engagement with the first gear wheel after the second set of engagement members has engaged the first gear wheel such that each of the engagement members in the first set engages the second gear wheel with a second engagement face.

44. **(New)** A method according to claim 42, engaging one of the first and second gear wheels such that the backlash between the first and second sets of engagement members and the drive formations when moving between acceleration and deceleration is less than or equal to four degrees when one of the first and second gear wheels is engaged by the first and second sets of engagement members.

45. **(New)** A method according to claim 42, wherein the actuator assembly includes a shift fork assembly and the method includes moving the first and second sets of engagement members independently of each other by action of the shift fork assembly.

46. **(New)** A method according to claim 45, wherein the shift fork assembly includes a shift fork and resilient means for connecting the first and second sets of engagement members to the shift fork, including moving the first and second sets of engagement members via the resilient means when the shift fork is actuated.

47. **(New)** A method according to claim 45, wherein engaging the second gear wheel with the first and second sets of engagement members includes moving the first and second sets of engagement members in a first direction along the longitudinal axis of the first shaft into engagement with the second gear wheel by action of the shift fork assembly, and wherein moving the first set of engagement members into engagement with the first gear wheel includes moving the first set of engagement members in a second direction along the longitudinal axis of the first shaft into engagement with first gear wheel by action of the shift fork assembly.

48. **(New)** A method according to claim 46, including biasing the first set of engagement members towards the first gear wheel while it is drivingly engaged with the second gear.

49. **(New)** A method according to claim 42, including providing a transmission system having at least one further shaft.

Appl. No. : 10/555,728
Filing date : January 6, 2006

50. (New) A method according to claim 42, including providing a transmission system wherein each member in the first and second sets of engagement members has a substantially rigid body such that the first and second engagement faces in a fixed relationship to one another.